

Axiz SB-1™



Product Specifications

Construction	Industrial grade NEMA 4 metal housing
Dimensions	12" L x 8" W x 4" D (30cm x 20cm x 10cm)
Weight	7.5 lbs (3.4 kg)
Interface	USB, RS232, RS485, Optional External BlueTooth
Memory	16,000 Tags
Approvals	FCC, Part 15c, ISO 11784 & 11785 compliant IC, CCIA, EN 30-330 compliant
Frequency	ISO Reader at 134.2 kHz
Technology Reads	FDXB, FDXA, HDX
Capablities	Self Tuning, Multiple Reader Synchronization, Multiple Communication Ports
Read Range	4 feet (1.2m) at optimal tag orientation User environment and antenna configuration may affect read range
Operating Temperature Range	-22° to 158° F -30° to 70° C
Humidity Range	10% to 90% non-condensing
Power	100-240 VAC, 47-63 Hz Optional 12 VDC external battery connection AC or DC
Display	LCD & LED

Warranty

The Axiz SB-1 reader is warranted for one year from the date of purchase against defects in materials and workmanship when used as directed. Use of the reader for functions other than RFID tag scanning may permanently damage the components and void the warranty. See official warranty statements in product manual for full details.

Accessories

Item	Part #	Item	Part #
Small Panel Antenna	AN7004	Left Headgate Antenna	AN7003
Large Panel Antenna	AN7002	Right Headgate Antenna	AN7001
Headgate Antenna Kit	AN7005	BlueTooth Kit	AC7054

Manufactured by:
Destron Fearing - 490 Villaume Ave
South St. Paul, MN 55075
Customer Service: 1-800-328-0118
www.destronfearing.com



Destron Fearing™

© 2010 Destron Fearing
950-0074-001