

# HD.Tag Family

(HDX)



# Product Specifications

Sizes	Dimensions	Individual Weight
HD.Tag Tamper Evident	1.2" diameter x .54"D (3cm x 1.4cm)	0.26 oz (7.3g)
HD.Tag Non-Tamper Evident	1.2" diameter x .45"D (3cm x 1.2cm)	0.26 oz (7.3g)
Standard Stud	1.1" diameter (2.8cm)	0.07 oz (2.0g)
Colors	Yellow	White
Construction	High-grade polyurethane	
Read Range	Up to 4 feet (1.2m) at optimal tag orientation depending on system use	
Application Temperature Range	0° to 122° F	-18° to 50° C
Approvals	ISO 11784, ISO 11785, ICAR USDA	
Power	Passive; can be read by all ISO-compliant readers	
Infecta + Guard	Active ingredients are 1.1 Hexamethylenebis [5-(4-Chlorophenyl) Biguanide] Digluconate	

## Warnings

Infect+Guard is self-activating upon application of the stud. Store in a cool, dry place. Do not allow stud to be exposed to moisture prior to application.

## Warranty

HD.tags are warranted for one year from the date of purchase against defects in materials and workmanship when used as directed

HD.TAG® (HDX) RFID SETS	Product Code
UNIVERSAL HD.TAG SET Round Stud	THDSet
UNIVERSAL HD.TAG Hog Max Stud	THMHDSet
UNIVERSAL HD.TAG Litter Max Stud	TLMHDSet
EXTRA LARGE COMBO	THDCSet
EXTRA LARGE COMBO - w Male Stud Panel	THDCZ
EXTRA LARGE CHOICESET™	HDXLCHSet
EXTRA LARGE CHOICESET™ Pair	HDXLCHSetP
TAMPER EVIDENT EXTRA LARGE CHOICESET™	THDXLCHS
TAMPER EVIDENT EXTRA LARGE CHOICESET™ w/ Panel Stud	THDXLCHZ
EXTENDED CHOICESET™	HDEXCHSet
EXTENDED CHOICESET™ w/ Panel Stud	HDEXCHZ
LARGE CHOICESET™	HDLGCHSet
LARGE CHOICESET™ w/ Panel Stud	HDLGCHZ

Manufactured by:  
 Destron Fearing - 490 Villaume Ave  
 South St. Paul, MN 55075  
 Customer Service: 1-800-328-0118  
 www.destronfearing.com

