

## Small Panel Antenna

Construction	Industrial grade polycarbonate, IP 67 Rated	
Dimensions	23" L x 17½" W x 1¼" D (58.5 cm x 44.5 cm x 3.2 cm)	
Weight	8 lbs (3.6 kg)	
Approvals	IEE STD C95.1 (1999), FCC & IC when used w/ Axiz Reader, CCIA, EN 300-330	
Frequency	ISO 134.2 kHz	
Read Range	3 feet (0.9m) at optimal orientation. User environment may affect read range	
Operating Temperature Range	-22° to 122° F	-30° to 50° C

## Large Panel Antenna

Construction	Industrial grade polycarbonate, IP 67 Rated	
Dimensions	44" L x 28" W x 1¼" D (112 cm x 71 cm x 3.2 cm)	
Weight	24 lbs (10.9kg)	
Approvals	IEE STD C95.1 (1999), FCC & IC when used w/ Axiz Reader, CCIA, EN 300-330	
Frequency	ISO 134.2 kHz	
Read Range	4 feet (1.2m) at optimal orientation. User environment may affect read range	
Operating Temperature Range	-22° to 122° F	-30° to 50° C

## Chute Antenna

Construction	Fully potted in industrial grade 2.5" PCV pipe. IP 67 Rated	
Dimensions	34" L x 2.5" diameter (87cm x 6.5cm)	
Weight	8.6lbs (3.9kg)	
Approvals	IEE STD C95.1 (1999), FCC & IC when used w/ Axiz Reader, CCIA, EN 300-330	
Frequency	ISO 134.2 kHz	
Read Range	Up to 16 inches at optimal tag orientation, 10 inches for ALL tag orientations User environment may affect read range	
Operating Temperature Range	-22° to 122° F	-30° to 50° C

## Warranty

Destron Fearing Antennas are warranted for one year from the date of purchase against defects in materials and workmanship when used as directed. Use of the reader for functions other than RFID tag scanning may permanently damage the components and void the warranty. See official warranty statements in product manual for full details.

Manufactured by:  
Destron Fearing - 490 Villaume Ave  
South St. Paul, MN 55075  
Customer Service: 1-800-328-0118  
www.destronfearing.com

