

RFID



Button



Combo

ChoiceSet™

Product Specifications

Product Class	Dimensions	Individual Weight
RFID Buttons		
HD.Tag™(HDX) Button Tamper Evident	1.2" diameter x .54"D (3cm x 1.4cm)	0.26 oz (7.3g)
HD.Tag (HDX) Button Non-Tamper Evident	1.2" diameter x .45"D (3cm x 1.2cm)	0.26 oz (7.3g)
e.Tag™(FDX) Button Tamper Evident	1.2" diameter x .54"D (3cm x 1.4cm)	0.29 oz (8.2g)
e.Tag (FDX) Button Non-Tamper Evident	1.2" diameter x .45"D (3cm x 1.2cm)	0.29 oz (8.2g)
e.Tag (FDX) Button Sheep/Goat	1.0" diameter x .2" D (2.5cm x 1.4cm)	0.13 oz (3.8g)
Combo RFID Tags		
HD Combo Tag Extra Large Tamper Evident	4.3" L x 2.8" W (11cm x 7cm)	0.56 oz (16.0g)
HD Combo Tag Extra Large Non-Tamper Evident	4.3" L x 2.8" W (11cm x 7cm)	0.56 oz (16.0g)
HD Combo Tag Large Tamper Evident	3.0" L x 2.2" W (7.6cm x 5.7cm)	0.40 oz (11.0g)
e. Combo Tag Extra Large Tamper Evident	4.3" L x 2.8" W (11cm x 7cm)	0.68 oz (19.2g)
e. Combo Tag Extra Large Non-Tamper Evident	4.3" L x 2.8" W (11cm x 7cm)	0.68 oz (19.2g)
e. Combo Tag Large Tamper Evident	3.0" L x 2.2" W (7.6cm x 5.7cm)	0.46 oz (13.0g)
Choice Set RFID Button w/ Panel Tag		
Extra Large	4" L x 3" W (12cm x 7.6cm)	0.38 oz (10.7g)
Extra Large Tamper Evident	4" L x 3" W (12cm x 7.6cm)	0.45 oz (12.7g)
Extended	3¾" L x 2½" W (9.5cm x 6.4cm)	0.25 oz (7.0g)
Large	2¾" L x 2¼" W (7.0cm x 5.7cm)	0.19 oz (5.3g)
Large Tamper Evident	2¾" L x 2¼" W (7.0cm x 5.7cm)	0.18 oz (5.1g)
Studs		
Standard Stud	1.1" diameter (2.8cm)	0.07 oz (2.0g)
LG Panel Stud	2.7" L x 2.2"w (6.9cm x 5.6cm)	0.20 oz (5.7g)
RFID BUTTON Colors	Yellow, White, Orange, Pink	
Panel Colors	Orange, Yellow, White, Purple, Red, Blue, Green, Pink, Black	
Construction	High-grade polyurethane	

Read Range Up to 4 feet (1.2m) at optimal tag orientation depending on system used

Application Temperature Range

HD.Tag HDX Tags	0° to 122° F	- 18° to 50° C
e.Tag FDX Tags	- 31° to 122° F	- 35° to 50° C

Approvals ISO 11784, ISO 11785, ICAR USDA
e.tag line CCIA

Power Passive; can be read by all ISO-compliant readers

Infecta + Guard Active ingredients are 1.1 Hexamethylenebis
[5-(4-Chlorophenyl) Biguanide] Digluconate

Warnings
Infect+Guard is self-activating upon application of the stud. Store in a cool, dry place. Do not allow stud to be exposed to moisture prior to application.

Warranty
Destron Fearing Tags are warranted for one year from the date of purchase against defects in materials and workmanship when used as directed

Use the ProGrip Applicator to Optimize Retention

Manufactured by:
Destron Fearing - 490 Villaume Ave
South St. Paul, MN 55075
Customer Service: 1-800-328-0118
www.destronfearing.com



Destron Fearing™